



CAT 6A NETWORK MODULE **5210-6MA**

APPLICATION

- Supports up to **6** data outlets and is designed for simplified cross connect signal distribution.

FEATURES

- CAT 6A data network module.
- Compatible with CAT 6A channel performance.
- Easily installed with finger-actuated latches. Just click the latches in to the holes on the back of the box and the installation is complete.

TRANSMISSION PERFORMANCE

- Meet all requirements specified in channel requirement of: ISO/IEC 11801, Class E_A.

ELECTRICAL SPECIFICATIONS

- Electrical Insulation Resistance : 500 MΩmin. @ 100V D.C.
- Dielectric Withstanding Voltage : 1000V D.C. or A.C. Peak Contact to Contact @ 60Hz for 1 minute.

MECHANICAL SPECIFICATIONS

- Insertion / Extraction Life : 750 Cycles Minimum.
- IDC Wire Gauge : 22 ~ 24 AWG.

PHYSICAL SPECIFICATIONS

- UL 1863 safety listed.
- UL 94V-0 fire retardant plastic.
- Housing : High-Impact, Flame-Retardant Plastic, UL 94V-0.
- Spring Wire : Phosphor Bronze Alloy Plated With 50 micro-inch of Gold.
- IDC : Phosphor Bronze Alloy With 100 micro-inch 100% Sn Alloy.
- Bracket : Metal.
- Dimensions: 164.4mm(W) x 75.0mm(H) x 34.2mm(D).

